



Mini-Candelabra

Mini-Candelabra

Bright, white light with higher performance for accent lighting. Halogen Mini Candelabra T4 Capsule lamps provide bright, white light for decorative and accent lighting and general illumination. Offered in T4 bulb size with mini candelabra base configurations. These lamps offer a rated average life ranging from 1000 to 2000 hours depending upon the product. Rated average life is the length of operation (in hours) at which point an average of 50% of the lamps will still be operational and 50% will not.

Benefits

- Compact size fits most decorative, accent and specialty fixtures.
- Available in a variety of wattages to meet most application needs.

Features

- Bright, white light.
- Must always be used in an enclosed fixture.
- 120 volt types require a fixture specifically designed for 120 volt operation. Never interchange 12 and 120 volt types.
- Available in 50, 75, 100, 150, 250 and 500 Watts.

Application

- Ideal for indoor decorative and accent lighting such as wall sconces, undercabinet lighting, and jewelry display cabinets. Not for use in low voltage fixtures.


Mini-Candelabra

Versions



E11, T4, Clear

Dimensional drawing



Product

BC50Q/CL 120V 12/1PK

BC150Q/CL ETG 120V 12/1PK

BC100Q/CL ESN 12/1P

Operating and electrical

Voltage (Nom) 120 V

General information

Cap-Base E11

Operating Position UNIVERSAL

Rated Lifetime (Hours) 1000 h

Light technical

Color Rendering Index (Nom) 100

Mechanical and housing

Bulb Finish Clear

Bulb Shape T-4

Operating and electrical

Order Code	Full Product Name	Power (Nom)
924711136303	BC50Q/CL 120V 12/1PK	50 W
926000850097	BC150Q/CL ETG 120V 12/1PK	150 W

Order Code	Full Product Name	Power (Nom)
926000850098	BC100Q/CL ESN 12/1P	100 W

Light technical

Mini-Candelabra

Order Code	Full Product Name	Correlated Color Temperature (Nom)	Luminous Flux (Nom)
924711136303	BC50Q/CL 120V 12/1PK	-	-
926000850097	BC150Q/CL ETG 120V 12/1PK	2800 K	2800 lm

Order Code	Full Product Name	Correlated Color Temperature (Nom)	Luminous Flux (Nom)
926000850098	BC100Q/CL ESN 12/1P	2800 K	1600 lm

