



Energy saving elegance with improved lumens and design versatility

Candle LED

Philips Candle Dimmable LED Lamps offer decorative energy saving ambience with the elegant effect of incandescent candles. Available in bent, blunt and flame tip candles, their unique design provides light in all directions, giving lighting designers a long life alternative to standard incandescent sources.

Benefits

- Long life properties-- lowers maintenance costs by reducing re-lamp frequency
- Installs into existing candelabra and medium-base fixtures
- Will not fade colors, avoids inventory spoilage
- Contains no mercury
- Emits virtually no UV/IR light in beam
- 3-year or 5-year limited warranty depending upon operating hours

Features

- Dimmable* and non-dimmable versions available
- Clear design available in bent, blunt and flame tip
- 25,000-hour rated average life⁺ for 3.5W Philips LED candle
- ^{*}Dimmable when using leading edge dimmers (see Philips Website: www.philips.com/ledtechguide for compatible leading edge dimmers.)
- ⁺Rated average life based on engineering testing and probability analysis.

Candle LED

Application

- Ideal for wall sconces, chandeliers and decorative lighting in retail, office, and hospitality spaces.

Versions



E14 T 25mm Frosted





E14 T 25mm Frosted



E14 T 25mm Frosted

Dimensional drawing



Product	D	C
LED 25W T25 E14 WW FR ND 1SRT4	25 mm	71 mm
Corepro LED T25 ND 3.2-25W E14 827	25 mm	71 mm

Product	D	C
LED 15W T25 E14 WW FR ND RF 1SRT6	25 mm	59 mm
LED 7W T25 E14 WW FR ND 1SRT6	25 mm	59 mm
Corepro LED T25 ND 1.7-15W E14 827	25 mm	59 mm
LED 15W T25 E14 WW FR ND RF 1SRT6 UK	25 mm	59 mm

Candle LED

Controls and Dimming

Dimmable	No
----------	----

Operating and Electrical

Input Frequency	50 to 60 Hz
Voltage (Nom)	220-240 V
Starting Time (Nom)	0.5 s

General Information

Cap-Base	E14
Nominal Lifetime (Nom)	15000 h
Switching Cycle	50000X

Light Technical

Color Code	827
Correlated Color Temperature (Nom)	2700 K
Color Rendering Index (Nom)	80
Llmf At End Of Nominal Lifetime (Nom)	70 %

Mechanical and Housing

Bulb Finish	Frosted
Bulb Shape	T25

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h
929001325702	Corepro LED T25 ND 1.7-15W E14 827	2 kWh
929001325755	LED 15W T25 E14 WW FR ND RF 1SRT6	2 kWh
929001325796	LED 15W T25 E14 WW FR ND RF 1SRT6 UK	2 kWh
929001325802	Corepro LED T25 ND 3.2-25W E14 827	4 kWh
929001325855	LED 25W T25 E14 WW FR ND 1SRT4	4 kWh
929002401355	LED 7W T25 E14 WW FR ND 1SRT6	1 kWh

Operating and Electrical

Order Code	Full Product Name	Wattage Equivalent	Power (Rated) (Nom)
929001325702	Corepro LED T25 ND 1.7-15W E14 827	15 W	1.7 W
929001325755	LED 15W T25 E14 WW FR ND RF 1SRT6	15 W	1.7 W
929001325796	LED 15W T25 E14 WW FR ND RF 1SRT6 UK	15 W	1.7 W

Order Code	Full Product Name	Wattage Equivalent	Power (Rated) (Nom)
929001325802	Corepro LED T25 ND 3.2-25W E14 827	25 W	3.2 W
929001325855	LED 25W T25 E14 WW FR ND 1SRT4	25 W	3.2 W
929002401355	LED 7W T25 E14 WW FR ND 1SRT6	7 W	0.9 W

Light Technical

Order Code	Full Product Name	Beam Angle (Nom)	Luminous Flux (Nom)
929001325702	Corepro LED T25 ND 1.7-15W E14 827	240 °	150 lm
929001325755	LED 15W T25 E14 WW FR ND RF 1SRT6	240 °	150 lm
929001325796	LED 15W T25 E14 WW FR ND RF 1SRT6 UK	240 °	150 lm

Order Code	Full Product Name	Beam Angle (Nom)	Luminous Flux (Nom)
929001325802	Corepro LED T25 ND 3.2-25W E14 827	160 °	250 lm
929001325855	LED 25W T25 E14 WW FR ND 1SRT4	160 °	250 lm
929002401355	LED 7W T25 E14 WW FR ND 1SRT6	240 °	70 lm

Temperature

Order Code	Full Product Name	T-Case Maximum (Nom)
929001325702	Corepro LED T25 ND 1.7-15W E14 827	55 °C
929001325755	LED 15W T25 E14 WW FR ND RF 1SRT6	55 °C
929001325796	LED 15W T25 E14 WW FR ND RF 1SRT6 UK	55 °C

Order Code	Full Product Name	T-Case Maximum (Nom)
929001325802	Corepro LED T25 ND 3.2-25W E14 827	80 °C
929001325855	LED 25W T25 E14 WW FR ND 1SRT4	80 °C
929002401355	LED 7W T25 E14 WW FR ND 1SRT6	50 °C

Candle LED

