



# UniStrip G4

## BCP386 12LED 40K 24V 60 L30 DMX

UniStrip G4 - 210 lm - 3 W - 4000 K

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

### Warnings and Safety

- For outdoor use only

### Product data

General information		Power Factor (Min)		0.9	
Light source color	Neutral white				
Driver included	No				
Controls and dimming					
Optical cover/lens type	Clear glass	Dimmable	Yes		
Control interface	Dynamic DMX				
Mechanical and housing					
Connection	2 Push-in connector 5-pole	Housing Material	Aluminum extruded		
Cable	2 cables 0.15m with connectors 5-pole	Optical cover/lens material	Polymethyl methacrylate		
Protection class IEC	Safety class III	Overall length	300 mm		
CE mark	CE mark	Overall width	25.4 mm		
		Overall height	71.6 mm		
Operating and electrical		Color	Dark gray		
Input Voltage	24 DC V				
Input Frequency	- Hz				

# UniStrip G4

## Approval and application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [ 1 J]

## Initial performance (IEC compliant)

Initial luminous flux (system flux)	210 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	70 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	80
Initial input power	3 W
Power consumption tolerance	+/-10%

## Application conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

## Product data

Full product code	871951451366299
Order product name	BCP386 12LED 40K 24V 60 L30 DMX
EAN/UPC - Product	8719514513662
Order code	911401780012
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	911401780012
Net Weight (Piece)	0.360 kg



## Dimensional drawing



BCP386 12LED 40K 24V 60 L30 DMX

