



Solar Panel Sub System

200W 36V Panel subsystem Vmpp 38.99V

A Range of Solar panels from 20 W to 325 W specially designed for Philips Solar Street lighting, Flood lighting and Solar Indoor Systems

Product data

General Information		Dimensions (Height x Width x Depth)	
CE mark	CE mark	40 x 992 x 1318 mm	
Warranty period	3 years	Approval and Application	
Operating and Electrical		Ingress protection code	IP67 [Dust penetration-protected, watertight]
Panel type	Poly crystalline	Product Data	
Panel voltage	36 V	Order product name	200W 36V Panel subsystem Vmpp 38.99V
Panel peak wattage	200 W	Full product name	200W 36V Panel subsystem Vmpp 38.99V
Cable connection kit	Included	Full product code	872016972924799
Cable	Cable 1.0 m 4.0 sqmm with Molex Connectors	Order code	911401804102
Temperature		Material Nr. (12NC)	911401804102
Ambient temperature range	-40 to +85 °C	Numerator - Quantity Per Pack	1
Mechanical and Housing		EAN/UPC - Product/Case	8720169729247
Overall length	1,318 mm	Numerator - Packs per outer box	30
Overall width	992 mm	EAN/UPC - Case	8720169729247
Overall height	40 mm		

Solar Panel Sub System

Dimensional drawing

