



Electronic digital control ignitor for HID lamp circuits

SU 42-S

HID ignitors for series systems


Product data

General information	
Application Code	42-S
Operating and electrical	
Input Voltage	220 to 230 V
Input Frequency	50 to 60 Hz
Igniton Type	Series
Response Voltage	198 V
Mains Voltage Performance (AC)	-8% - +6%
Mains Voltage Safety (AC)	-10% - +10%
Power Losses (Nom)	3 W
Wiring	
Ballast Contact Wire Cross Section	0.50-2.50 mm ²
Connector Type	Screw
Temperature	
T-Ambient (Nom)	75 °C
T-Case Maximum (Max)	105 °C

Mechanical and housing	
Housing	PC UL94V-2
Approval and application	
Approval Marks	CE marking China Quality Certificate CB Certificate
Product data	
Full product code	697013372897000
Order product name	SU 42-S
EAN/UPC - Product	6970133728970
Order code	913710016213
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	20
Material Nr. (12NC)	913710016213
Net Weight (Piece)	0.200 kg

Electronic digital control ignitor for HID lamp circuits

Dimensional drawing



Product	A2	C1	A1	B1
SU 42-S	63.4 mm	34 mm	96 mm	45 mm

SU 42-S

