



HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

BSN 70L 300I TS

The HID Basic Semi-Parallel ballast is an impregnated (HID standard) electromagnetic copper/iron ballast for use with an external ignitor for HID lamps.


Product data

General Information	
Application Code	L300 ITS
Operating and Electrical	
Input Voltage	220 V
Input Frequency	50 Hz
Power Factor 100% Load (Min)	0.40
Mains Voltage Performance (AC)	-8% - +6%
Mains Voltage Safety (AC)	-10% - +10%
Input Current with PF Correction	0.98 A
Input Current without PF Correction	0.98 A
Wiring	
Connector Type	Screw
System characteristics	
Rated Ballast-Lamp Power	70 W

Temperature	
T-Winding (Max)	130 °C
Delta-T Normal Conditions	75 °C
Approval and Application	
Approval Marks	CE marking CCC certificate
Product Data	
Full product code	694818229948200
Order product name	BSN 70L 300I TS
EAN/UPC - Product	6948182295408
Order code	913710106942
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	913710106942
Net Weight (Piece)	1.100 kg

HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

Dimensional drawing



Product	D1	C1	A1	A2	B1
BSN 70L 300I TS	6.2 mm	51.5 mm	117.0 mm	110 mm	57.1 mm

BSN 70 L300 ITS

