

BTA EM ballasts for TL Fluorescent lamps

BTA 58W 230V B2 SC

This efficient, reliable, long-life electromagnetic ballast for TL-D fluorescent lamps features a balanced combination of essential characteristics, thus allowing a wide variety of standard applications.

Product data


General Information		Temperature	
Application Code	58W	T-Storage (Max)	80 °C
Design	B2	T-Storage (Min)	-40 °C
		T-Winding (Max)	130 °C
		Delta-T Normal Conditions	55 °C
Operating and Electrical		Mechanical and Housing	
Input Voltage	230 V	Housing	L 195x39x28
Input Frequency	50 Hz		
Mains Voltage Performance (AC)	-8%~+6%	Approval and Application	
Mains Voltage Safety (AC)	-10%~+10%	Energy Efficiency Index	B2
Power Factor with PF Compensation	0.85	Approval Marks	CE marking ENEC certificate
Power Factor without PF Compensation (Nom)	0.45		
Power Losses (Nom)	10.4 W	Product Data	
		Full product code	871016308603330
		Order product name	BTA 58W 230V B2 SC
		EAN/UPC - Product	8710163150734
		Order code	913710124050
		Numerator - Quantity Per Pack	1
		Numerator - Packs per outer box	24
		Material Nr. (12NC)	913710124050
Wiring			
Wire Striplength	8.0 mm		
Ballast Contact Wire Cross Section	0.50-1.00 mm ²		
Connector Type	Screw		
System characteristics			
Rated Ballast-Lamp Power	58 W		

BTA EM ballasts for TL Fluorescent lamps

Net Weight (Piece)

0.949 kg

Dimensional drawing



BTA 58W 230V B2 SC

Product	D1	C1	C3	A1	A2	A3	A4	B1	B2
BTA 58W	4.0	28.0	1.2	195.0	180.0	48.0	110.0	39.0	20.0
230V B2 SC	mm	mm	mm	mm	mm	mm	mm	mm	mm

