



# PrimaVision Mini for CDM

## HID-PV m 1X020/S CDM LPF 220-240V

Miniature HID electronic gear for PGJ5 CDM lamps – freeing up the boundaries of creativity and innovation in luminaire design

### Product data

General Information	
Application Code	LPF
Lamp Type	CDM
Suitable For Outdoor Use	No
Number of Products on MCB (16A Type B) (Nom)	36
Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Minimum Mains Voltage Operation (Min)	198 V
Ignition Voltage (Max)	1.4 kV
Ignition Voltage (Min)	1.2 kV
Mains Voltage Performance (AC)	198-254V
Mains Voltage Safety (AC)	180-264V
Earth Leakage Current (Max)	0.25 mA
Inrush Current Width	0.4 ms
Constant Wattage Deviation	-3%/+3%
Inrush Current Peak (Max)	30 A


Wiring	
Cable Capacity Output Wires Mutual (Nom)	200 pF
System characteristics	
Rated Ballast-Lamp Power	20 W
Temperature	
T-Ambient (Max)	50 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	80 °C
T-Storage (Min)	-25 °C
T-Case Lifetime (Nom)	65 °C
T-Case Maximum (Max)	75 °C
Mechanical and Housing	
Housing Material	Plastic
Housing	/S
Approval and Application	
Active Temperature Protection	Yes
Vibration Standard	IEC68-2-6 F c
Bumps Standard	IEC 60068-2-29 Eb

## PrimaVision Mini for CDM

Approval Marks	F-Marking CE marking VDE certificate
Hum And Noise Level	30 dB(A)
<b>Product Data</b>	
Full product code	871016306267900
Order product name	HID-PV m 1X020/S CDM LPF 220-240V
EAN/UPC - Product	8710163149608

Order code	913712005214
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	913712005214
Net Weight (Piece)	0.199 kg

### Dimensional drawing



HID-PV m 1x020/S/S CDM LPF 220-240V

Product	D1	C1	A1	A2	B1
HID-PV m 1X020/S CDM LPF 220-240V	4.2 mm	30.5 mm	97.3 mm	88.3 mm	43.3 mm

