



# HID-PV/DV economy for CPO-CDM

## HID-PV E 70 /S CDM 220-240V 50/60Hz

Certavision driver is an electronic driver for CPO or CDM Elite MW lamps – helps create an efficient white-light system.


### Product data

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Earth Leakage Current (Max)	0.5 mA
Inrush Current Width	0.33 ms
Input Current (Nom)	0.2 A
Inrush Current Peak (Max)	33 A
Wiring	
Cable Length From Device to Lamp	2 m
Temperature	
Ambient temperature range	-20 °C to 55 °C
T-Case Lifetime (Nom)	85 °C
Mechanical and Housing	
Housing	/S

Approval and Application	
Surge Protection (Common/Differential)	EN61547 (L-L 1kV, L-G 2kV) kV
Safety Standard	IEC 61347-2-11
Environmental Standard	ISO 14001
Approval Marks	CE marking
Product Data	
Order product name	HID-PV E 70 /S CDM 220-240V 50/60Hz
Full product name	HID-PV E 70 /S CDM 220-240V 50/60Hz
Full product code	871869642008900
Order code	913712008566
Material Nr. (12NC)	913712008566
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696420089
Numerator - Packs per outer box	12
EAN/UPC - Case	8718696420096

HID-PV/DV economy for CPO-CDM

Dimensional drawing



Product	D1	C1	A1	A2	B1	B2
HID-PV E 70 /S CDM 220-240V 50/60Hz	4 mm	31.6 mm	109.8 mm	98.7 mm	74.8 mm	63.7 mm

