

HID-Basic Semi-Parallel ballasts for MHN/CDM lamps

BMH 35L 300I TS

The HID Basic Semi-Parallel ballast is an impregnated (HID standard) electromagnetic copper/iron ballast for use with an external ignitor for metal-halide and CDM lamps.

Product data


General Information	
Application Code	L300 ITS
Operating and Electrical	
Input Voltage	220 V
Input Frequency	50 Hz
Power Factor 100% Load (Min)	0.85
Mains Voltage Performance (AC)	-8% - +6%
Mains Voltage Safety (AC)	-10% - +10%
Input Current with PF Correction	0.24 A
Input Current without PF Correction	0.53 A
Power Factor without PF Compensation (Nom)	0.40
Power Losses (Nom)	7.4 W
Wiring	
Connector Type	Screw

System characteristics	
Rated Ballast-Lamp Power	35 W
Temperature	
T-Winding (Max)	130 °C
Delta-T Normal Conditions	55 °C
Approval and Application	
Approval Marks	CE marking ENEC certificate CCC certificate
Product Data	
Full product code	697480505103800
Order product name	BMH 35L 300I TS
EAN/UPC - Product	6974805051038
Order code	913713200567
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	913713200567

HID-Basic Semi-Parallel ballasts for MHN/CDM lamps

Net Weight (Piece)	0.800 kg
--------------------	----------

Dimensional drawing



BMH 35L 300I TS

Product	D1	C1	A1	A2	B1
BMH 35L 300I TS	6.2 mm	51.5 mm	117.0 mm	102.0 mm	57.1 mm

