



# TL5 consumer products

## TL5 HE 21W WW 1PP/10

A TL5 lamp is 40% thinner and 5 cm shorter than corresponding TL-D lamp. The lamps are available in 3 wattages and in 2 colors (warm white and cool white)

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Correlated Color Temperature (Nom)	
Cap-Base	G5 [ G5]		3000 K
Life to 50% Failures Preheat (Nom)	24000 h	Luminous Efficacy (rated) (Nom)	90 lm/W
Features	na [ Not Applicable]	Color Rendering Index (Max)	85
System Description	High Efficiency	Color Rendering Index (Min)	80
LSF Preheat 2000 h Rated	99 %	Color Rendering Index (Nom)	>80
LSF Preheat 4000 h Rated	99 %	LLMF 2000 h Rated	96 %
LSF Preheat 6000 h Rated	99 %	LLMF 4000 h Rated	95 %
LSF Preheat 8000 h Rated	99 %	LLMF 6000 h Rated	94 %
LSF Preheat 16000 h Rated	97 %	LLMF 8000 h Rated	93 %
LSF Preheat 20000 h Rated	84 %	LLMF 12000 h Rated	92 %
		LLMF 16000 h Rated	91 %
		LLMF 20000 h Rated	90 %
Light Technical		Operating and Electrical	
Color Code	830 [ CCT of 3000K]	Power (Nom)	20.6 W
Luminous Flux (Nom)	2100 lm	Lamp Current (Nom)	0.165 A
Luminous Flux (Rated) (Nom)	1850 lm		
Color Designation	Warm White (WW)		
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	101 lm/W		

## TL5 consumer products

### Temperature

Design Temperature (Nom)	35 °C
--------------------------	-------

### Controls and Dimming

Dimmable	Yes
----------	-----

### Mechanical and Housing

Cap-Base Information	Green Plate
----------------------	-------------

### Approval and Application

Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	23 kWh

### Product Data

Full product code	871150089721325
Order product name	TL5 HE 21W WW 1PP/10
EAN/UPC - Product	8711500897213
Order code	927926283032
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	927926283032
Net Weight (Piece)	79.200 g
ILCOS Code	FDH-21/30/1B-L/P-G5-16/850


## Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL5 HE 21W WW 1PP/10	17 mm	849.0 mm	856.1 mm	853.7 mm	863.2 mm

## TL5 21W/830/GP HE

## Photometric data



LDPB\_TL5-HE8\_830-Spectral power distribution B/W



LDPO\_TL5-HE8\_830-Spectral power distribution Colour

# TL5 consumer products

## Lifetime



LDLE\_TL5-HE8\_0001-Life expectancy diagram

LDLE\_TL5-HE8\_0002-Life expectancy diagram



LDLM\_TL5-HE8\_0001-Lumen maintenance diagram

