



MSR Gold™ FastFit

MSR Gold™ 2000/1 FastFit 1CT/8

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR Gold™ FastFit can be operated in a lamp wattage range between 700W and 2500W.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Luminous Efficacy (rated) (Nom)	
Cap-Base	PGJX50 [PGJX50]		86 lm/W
Operating Position	UNIVERSAL [Any or Universal (U)]	Color Rendering Index (Nom)	90
Main Application	Entertainment	Operating and Electrical	
Life to 50% Failures (Nom)	750 h	Power (Nom)	2000 W
Light Technical		Lamp Current (Nom)	18.2 A
Luminous Flux (Min)	155000 lm	Ignition Supply Voltage (Max)	198 V
Luminous Flux (Nom)	172000 lm	Controls and Dimming	
Chromaticity Coordinate X (Nom)	329	Dimmable	Yes
Chromaticity Coordinate Y (Nom)	333		
Correlated Color Temperature (Nom)	5700 K		

MSR Gold™ FastFit

Mechanical and Housing

Cap-Base Information PGJX50

Luminaire Design Requirements

Bulb Temperature (Max) 950 °C

Pinch Temperature (Max) 500 °C

Product Data

Full product code 871869667944900

Order product name MSR Gold™ 2000/1 FastFit 1CT/8

EAN/UPC - Product 8718696679449

Order code 928410105114

Numerator - Quantity Per Pack 1

Numerator - Packs per outer box 8

Material Nr. (12NC) 928410105114

Net Weight (Piece) 138.000 g

Dimensional drawing



Product	D (max)	O	L (min)	L	L	C (max)	F
MSR Gold™ 2000/1 FastFit 1CT/8	34 mm	8 mm	66 mm	68 mm	67 mm	134 mm	50 mm

MSR Gold 2000/1 FastFit

