



LED MR16

6.4MR16/F35/3000 DIM 12V

Philips LED MR-16 lamps with single optic technology provide the look and color quality of traditional halogens while using a fraction of the energy. A perfect fit for spot lighting, they are compatible with most existing fixtures with MR16 GU5.3 holders and are designed as a retrofit replacement for halogen or incandescent spots.

Product data


General information		Lamp Current (Nom)	
Cap-Base	GU5.3 [GU5.3]		800 mA
EU RoHS compliant	Yes	Wattage Equivalent	42 W
Nominal Lifetime (Nom)	25000 h	Starting Time (Nom)	0.6 s
Switching Cycle	50000X	Warm Up Time to 60% Light (Nom)	0.6 s
Technical Type	6.4-35W	Power Factor (Nom)	0.7
		Voltage (Nom)	12 V
Light technical		Temperature	
Color Code	830 [CCT of 3000K]	T-Case Maximum (Nom)	100 °C
Beam Angle (Nom)	35 °		
Luminous Flux (Nom)	450 lm	Controls and dimming	
Luminous Intensity (Nom)	1000 cd	Dimmable	Yes
Color Designation	White (WH)		
Correlated Color Temperature (Nom)	3000 K	Mechanical and housing	
Luminous Efficacy (rated) (Nom)	70.31 lm/W	Bulb Finish	Frosted
Color Consistency	<6	Bulb Material	Aluminum
Color Rendering Index (Nom)	80	Bulb Shape	MR16 [2inch/50mm]
LLMF At End Of Nominal Lifetime (Nom)	70 %		
Operating and electrical		Approval and application	
Input Frequency	- Hz	Suitable For Accent Lighting	Yes
Power (Nom)	6.4 W	Energy Consumption kWh/1000 h	- kWh

LED MR16

Energy Certifications	Energy Star
Product data	
Order product name	6.4MR16/F35/3000 DIM 12V
EAN/UPC - Product	046677470340
Order code	929001152234

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001152234
Net Weight (Piece)	0.045 kg

Dimensional drawing



6.4MR16/F35/3000 DIM 12V

Product	D	C
6.4MR16/F35/3000 DIM 12V	51 mm	51 mm

Photometric data

