



Classic filament LEDbulbs



LED cla 120W G120 E27 WW FR ND RFSRT4

Featuring a classic heritage design, Classic filament LEDbulbs combine the familiar shapes of classic incandescent bulbs with the benefits of the long lasting LED technology. They deliver beautiful, decorative warm-white light while saving around 90% on energy costs compared with traditional light bulbs.

Product data

| General Information | |
|--|--------------------|
| Cap-Base | E27 |
| Nominal lifetime | 15,000 hour(s) |
| Switching Cycle | 20,000 |
| Rated Lifetime (Hours) | 15,000 hour(s) |
| Lighting Technology | LED |
| Flux measurement reference | Sphere |
| EU RoHS compliant | Yes |
| | |
| Light Technical | |
| Color Code | 827 [CCT of 2700K] |
| Color Code | 827 [CCT of 2700K] |
| Luminous Flux | 2,000 lm |
| Color Designation | Warm White (WW) |
| Correlated Color Temperature (Nom) | 2700 K |
| Luminous Efficacy (rated) (Nom) | 153.00 lm/W |
| Color Consistency | <6 |
| Color rendering index (CRI) | 80 |
| LLMF At End Of Nominal Lifetime (Nom) | 70 % |
| Flickering value (PstLM) - Flickering value as | 1 |
| per EN 61000-3-3 | |
| | |

| Stroboscopic effect visibility measure (SVM) | 0.4 |
|--|-------------|
| Photobiological safety according to EN 62471 | RG1 |
| | |
| Operating and Electrical | |
| Line Frequency | 50 to 60 Hz |
| Input Frequency | 50 to 60 Hz |
| Power Consumption | 13 W |
| Lamp Current (Nom) | 120 mA |
| Wattage Equivalent | 120 W |
| Starting Time (Nom) | 0.5 s |
| Warm-up time to 60% light | 0.5 s |
| Power Factor (Fraction) | 0.51 |
| Voltage (Nom) | 220-240 V |
| | |
| Temperature | |
| T-Case Maximum (Nom) | 55 ℃ |
| | |
| Controls and Dimming | |
| Dimmable | No |
| | |


Datasheet, 2024, March 14 data subject to change

Classic filament LEDbulbs

| Marshandard and Harrier | | |
|-------------------------------------|------------|--|
| Mechanical and Housing | | |
| Bulb Finish | Frosted | |
| Bulb Material | Glass | |
| Bulb Shape | G120 | |
| | | |
| Approval and Application | | |
| Energy Efficiency Class | D | |
| Energy Consumption kWh/1000 h | 13 kWh | |
| EPREL Registration Number | 374860 | |
| EyeComfort | Yes | |
| LED Innovations | EyeComfort | |
| | | |
| Application Conditions | | |
| can it be used in closed luminaires | No | |
| | | |


| Product Data | |
|---------------------------------|--------------------------------|
| Order product name | LED cla 120W G120 E27 WW FR ND |
| | RFSRT4 |
| Full product name | LED cla 120W G120 E27 WW FR ND |
| | RFSRT4 |
| Full product code | 871869976481400 |
| Order code | 929002372101 |
| Material Nr. (12NC) | 929002372101 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8718699764814 |
| Numerator - Packs per outer box | 4 |
| EAN/UPC - Case | 8718699764821 |
| | |

Dimensional drawing




| Product | D | С |
|---------------------------------------|--------|--------|
| LED cla 120W G120 E27 WW FR ND RFSRT4 | 124 mm | 177 mm |

Photometric data








Spectral Power Distribution Colour - LED cla 120W G120 E27 WW FR ND RFSRT4


Classic filament LEDbulbs


Photometric data



Light Distribution Diagram - LED cla 120W G120 E27 WW FR ND RFSRT4

Lifetime





Life Expectancy Diagram - LED cla 120W G120 E27 WW FR ND RFSRT4

Lumen Maintenance Diagram - LED cla 120W G120 E27 WW FR ND RFSRT4



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.