



Energy Saver GU24

EL/mdTQS 18W GU24

Looking for an energy saver that doesn't look like one? The Philips Energy Saver family provides energy-efficient lighting options that don't just deliver similar light as your standard incandescent light bulb, they also have the same classic shape. Try Philips Energy Savers and see how they truly offer advanced lighting to meet your needs.

Product data

| General information | | Power (Nom) | |
|---------------------------------------|---------------------|---------------------------------|-------------------|
| Cap-Base | GU24 [GU24] | Lamp Current (Nom) | 290 mA |
| Nominal Lifetime (Nom) | 10000 h | Warm Up Time to 60% Light (Min) | 5 s |
| Switching Cycle | 5000X | Warm Up Time to 60% Light (Max) | 40 s |
| Rated Lifetime (Hours) | 10000 h | Power Factor (Nom) | 0.55 |
| | | Voltage (Nom) | 110-127 V |
| Light technical | | Controls and dimming | |
| Color Code | 827 [CCT of 2700K] | Dimmable | No |
| Luminous Flux (Nom) | 1250 lm | | |
| Luminous Flux (Rated) (Nom) | 1250 lm | Mechanical and housing | |
| Color Designation | Warm White (WW) | Bulb Shape | EL/mdTQS |
| Lumen Maintenance 2000 h (Nom) | 85 % | | |
| Lumen Maintenance 5000 h (Nom) | 70 % | Approval and application | |
| Chromaticity Coordinate X (Nom) | 459 | Mercury (Hg) Content (Max) | 2 mg |
| Chromaticity Coordinate Y (Nom) | 412 | Energy Consumption kWh/1000 h | 18 kWh |
| Correlated Color Temperature (Nom) | 2700 K | | |
| Luminous Efficacy (rated) (Nom) | 67 lm/W | Product data | |
| Color Rendering Index (Nom) | 80 | Order product name | EL/mdTQS 18W GU24 |
| LLMF At End Of Nominal Lifetime (Nom) | 50 % | EAN/UPC - Product | 046677454203 |
| Operating and electrical | | Order code | 929689791301 |
| Input Frequency | 50 or 60 Hz | Numerator - Quantity Per Pack | 1 |

Energy Saver GU24

| | |
|---------------------------------|--------------|
| Numerator - Packs per outer box | 6 |
| Material Nr. (12NC) | 929689791301 |
| Copy Net Weight (Piece) | 0.070 kg |

Dimensional drawing



| Product | D (max) | C (max) | F (max) |
|-------------------|---------|----------|---------|
| EL/mdTQS 18W GU24 | 56.5 mm | 104.0 mm | 47 mm |

EL/mdTQS 18W GU24

