



# High Power GearUnits

## ECB330 MHN-LA2000W 360-415V FU

ZCM330 | GearUnits, MHN-LA | MASTER MHN-LA, 2000 W, 2166 W

Philips is one of the few companies able to provide total floodlight system solutions comprising all necessary elements – floodlight, lamp source and control gear unit. Our innovative high-power GearUnits are designed to meet our customers' need for a compact gear solution that is completely ready for installation. The pre-wired high-power control gear units are intended for use in combination with floodlights that are suitable for high-wattage HID lamps and cannot integrate electrical components because of limited space or high temperatures. A gear unit contains all electrical components (ballast, ignitors, capacitors), wiring and terminal blocks needed to ensure initial lamp ignition and proper operation of the lamp in stabilized current. The electromagnetic high-power GearUnits are available in both IP20 (ECB330) and IP65 (ECP330) versions. Within the GearUnits family there is also an electronic flicker-free ballast version (ECM330) available in IP20, which is suitable for the MVF403 MHN-LA 1000 W and MVF404 MHN-SE HO 2000 W ArenaVision floodlights. The ArenaVision floodlight family is specially designed for TV broadcasts from indoor and outdoor sports facilities. Electronic-ballast GearUnits completely eliminate the flicker effect, thereby guaranteeing perfect images filmed with super-slow-motion cameras.

### Product data

General Information	
Lamp family code	MHN-LA [MASTER MHN-LA]
Number of gear units	1 unit
Gear	CONV [Conventional]
Value ladder	Performance

Light Technical	
Number of light sources	1

  

Operating and Electrical	
Input Voltage	360 to 415 V
Line Frequency	50 Hz
Power Consumption	2,000 2,166 W

## High Power GearUnits

Connection	Screw connection block 3-pole
<b>Controls and Dimming</b>	
Dimmable	No
<b>Mechanical and Housing</b>	
Ingress protection code	IP20 [Finger-protected]
Net Weight (Piece)	17.900 kg
<b>Approval and Application</b>	
Energy Efficiency Index	A3
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-
EU RoHS compliant	Yes

Ambient temperature range	-30 to +55 °C
<b>Product Data</b>	
Order product name	ECB330 MHN-LA2000W 360-415V FU
Full product name	ECB330 MHN-LA2000W 360-415V FU
Full product code	871829106276900
Order code	910925726012
Material Nr. (12NC)	910925726012
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291062769
Numerator - Packs per outer box	1
EAN/UPC - Case	8718291062769
Product family code	ZCM330 [GearUnits]

### Dimensional drawing

