



# AluRoad gen2

## BGP025 LED147/730 II DW CLO-DDF2

LED147 | LED module 14700 lm, LED, 85 W, Power supply unit with DynaDimmer and constant light output (integrated), Distribution wide, Flat glass, 23° x 59° x 148°, Single layer powder coating, Programmable (via DALI or NFC) stand-alone dimming, Side-entry for diameter 48 to 60 mm

The AluRoad gen2 family is available in 2 versions, standard AluRoad gen2 and AluRoad gen2 Pro. These are available in 2 sizes, Mini and Medium. Standard AluRoad gen2 as BGP020 Mini and BGP025 Medium, AluRoad gen2 Pro as BGP021 Mini and BGP026 Medium. Standard AluRoad gen2 features a fixed spigot for both post top 0 degrees tilt and side entry with limited negative tilt. AluRoad gen2 Pro is equipped with an adjustable spigot allowing tilt settings in both post top and side entry, positive and negative. AluRoad gen2 enables you to easily upgrade your city's lighting and enjoy the benefits of LED technology, designated to further minimize Total Cost of Investment and Ownership. The family is ideally suited for both new build areas and streets as well as renovation of existing installations. This affordable family not only offers a clean and timeless design to blend in with the environment, but also brings high quality lighting and future proof solutions with significant energy and maintenance savings over a long operational life.

### Product data

General Information	
Lamp family code	LED147 [LED module 14700 lm]
Number of gear units	1 unit
Driver included	Yes
Light source engine type	LED
Value ladder	Value
Warranty period	5 years

Sustainability rating	Lighting for circularity
Light Technical	
Upward light output ratio	0
Luminous Flux	11,475 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	143 lm/W

## AluRoad gen2

Color rendering index (CRI)	70
Light source color	730 warm white
Luminaire light beam spread	23° x 59° x 148°
Optic type outdoor	Distribution wide
Effective projected area	0.032 m <sup>2</sup>

### Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Inrush current	45 A
Inrush time	0.27 ms
Power Consumption	85 W
Power Factor (Fraction)	0.98
Connection	Push-in connector 2-pole
Cable	-
Number of products on MCB of 16 A type B	10
Protection class IEC	Safety class II
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV differential mode and 8 kV common mode

### Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DynaDimmer and constant light output (integrated)
Control interface	Programmable (via DALI or NFC) stand-alone dimming
Constant light output	Yes

### Mechanical and Housing

Housing Material	Aluminum die cast
Reflector material	-
Optic material	Polymethyl methacrylate
Optical cover material	Glass
Fixation material	Stainless steel
Housing Color	Gray
Mounting device	Side-entry for diameter 48 to 60 mm
Optical cover shape	Flat
Optical cover finish	Clear
Overall length	592 mm
Overall width	230 mm
Overall height	112 mm
Dimensions (Height x Width x Depth)	112 x 230 x 592 mm

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Standard tilt angle posttop	0°
Standard tilt angle side entry	0°
Optical cover type	Flat glass
Net Weight (Piece)	4.400 kg

### Approval and Application

Flammability mark	-
CE mark	Yes
ENEC mark	ENEC mark
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Ambient temperature range	-40 °C to 50 °C

### Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0.43, 0.40) SDCM<5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

### Over Time Performance (IEC Compliant)


Control gear failure rate at median useful life 50000 h	5 %
Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 50000 h	L98
Lumen maintenance at median useful life* 100000 h	L95

### Product Data

Order product name	BGP025 LED147/730 II DW CLO-DDF2
Full product name	BGP025 LED147/730 II DW CLO-DDF2
Full product code	871951476911300
Order code	910925869114
Material Nr. (12NC)	910925869114
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

# AluRoad gen2

## Dimensional drawing



Dimensions (mm)						
Luminaire	A	B	C	D	E	G
Mini BGPO20	447	70	112	111	334	88
Medium BGPO25	592	70	112	111	481	88

