



RoadFlair ECO

BRP490L LED124/NW 80W DW2n PSA SP1

RoadFlair ECO, 12400 lm, 80 W, 740 neutral white, depends on driver (1-10V, DALI...), Safety class I

RoadFlair ECO is a newly designed road lighting product, set to meet customers' requirements, including high lumen efficacy for energy saving and sustainability, aesthetic design for nice shape and appearance, quality material and components for product reliability and long lifetime, professional optic for lighting application fulfilment, dimming and system control interface for improving municipal operations and offering future-proof features. RoadFlair ECO's competitive price would help on the acceleration of road lighting LED transformation, to more sustainable society and smarter city.

Product data

General Information		Line Frequency	
Gear	-	Line Frequency	50 or 60 Hz
Driver included	Yes	Inrush current	79 A
Service tag	Yes	Power Consumption	80 W
Light Technical		Power Factor (Fraction)	0.95
Luminous Flux	12,400 lm	Connection	Flying leads/wires
Correlated Color Temperature (Nom)	4000 K	Cable	Cable 0.3 m without plug 3-pole
Luminous Efficacy (rated) (Nom)	155 lm/W	Protection class IEC	Safety class I
Color rendering index (CRI)	70	Controls and Dimming	
Light source color	740 neutral white	Dimmable	Yes
Effective projected area	0.07 m ²	Control interface	depends on driver (1-10V, DALI...)
Operating and Electrical		Mechanical and Housing	
Input Voltage	220-240 V	Housing Material	Aluminium die-cast ADC1 - alloy grade (EN AC-47100)

RoadFlair ECO

Optical cover material	Polycarbonate
Housing Color	RAL7040
Overall length	543 mm
Overall width	132.5 mm
Overall height	103.5 mm
Dimensions (Height x Width x Depth)	104 x 133 x 543 mm
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Optical cover type	Polycarbonate bowl/cover UV-resistant
Net Weight (Piece)	2.690 kg

Approval and Application

Flammability mark	-
CE mark	Yes
Ambient temperature range	-40 °C to 50 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Power consumption tolerance	+/-10%

Product Data

Order product name	BRP490L LED124/NW 80W DW2n PSA SP1
Full product name	BRP490L LED124/NW 80W DW2n PSA SP1
Order code	911401647409
Material Nr. (12NC)	911401647409
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4

Dimensional drawing

