



UniString

BWS302 8LED 30K 24V S TM N10P20

UniString, 142 lm, 20 W, Warm white, 110° x 110°, Safety class III

UniString is a surface mounted, exterior-rated and compact sized architectural LED direct view string that is designed for architectural and media façade outdoor lighting applications. The robust mechanical design, easy installation and unique optical lenses make UniString ideal for buildings/media facades, bridges, arenas, theaters, amusement parks and recreational centers. Available in white, monochromatic colors, RGB, RGBW and tunable white. Available in symmetrical and asymmetrical optical distributions with DMX control option to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

General Information	
Light source replaceable	No
Driver included	No

Light Technical	
Luminous Flux	142 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	71 lm/W
Color rendering index (CRI)	80
Light source color	Warm white
Luminaire light beam spread	110° x 110°

Operating and Electrical	
Input Voltage	24 DC V
Line Frequency	- Hz
Power Consumption	20 W
Power Factor (Fraction)	1
Connection	Push-in connector 2-pole
Cable	2 meters long cable with 10 nodes, 200mm pitch and 2 connectors 2-pole
Protection class IEC	Safety class III

Controls and Dimming	
Dimmable	No

UniString

Control interface	-
Mechanical and Housing	
Housing Material	Polycarbonate
Optical cover material	Polycarbonate
Housing Color	Black
Overall length	57.2 mm
Overall width	15.5 mm
Overall height	60.1 mm
Dimensions (Height x Width x Depth)	60 x 16 x 57 mm
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Optical cover type	Polycarbonate bowl/cover clear
Net Weight (Piece)	0.708 kg
Approval and Application	
Glow-wire test	Temperature 750 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes

Ambient temperature range	-40 to +50 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	4 SDCM
Power consumption tolerance	+/-10%
Product Data	
Order product name	BWS302 8LED 30K 24V S TM N10P20
Full product name	BWS302 8LED 30K 24V S TM N10P20
Full product code	872016974799999
Order code	911401753892
Material Nr. (12NC)	911401753892
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169747999
Numerator - Packs per outer box	12
EAN/UPC - Case	8720169747999

Dimensional drawing

