

# Australia and New Zealand Certificate of Suitability

**Certificate**  
ULL-103699

**Issue date**  
2024-12-17

**Expiration date**  
2029-12-17



[www.jasanz.org/register](http://www.jasanz.org/register)

This is to acknowledge that

**Signify Netherlands B.V.**

High Tech Campus 48, EINDHOVEN 5656 AE  
Netherlands

has had

**Electronic Control gear for LED modules  
{component for building in}**

[refer following page(s) for models list]

evaluated and meets the requirements of the standard(s)

**AS 61347.2.13:2018;  
AS/NZS 61347.1:2016+A1**

ANZ Certification Scheme requirements.



Stuart Foster (Certification Officer)

Certification Body:

UL International New Zealand Limited,  
54 Tarndale Grove, Albany, Auckland 0632, New Zealand.

Issued for use in Australia and New Zealand only.  
All dates are in Year-Month-Day format (YYYY-MM-DD).

# Australia and New Zealand Certificate of Suitability

**Certificate No:** ULL-103699

**Date of Issue/Revision:** 2024-12-17

**Trade Name or Trademark:** PHILIPS, SIGNIFY

**Risk Class / NSW Declared Class:** EESS OUT OF SCOPE - Non-prescribed / non-declared

**IEC Standard Country Differences:** AU and NZ

**Certification Marking:** The RCM may be applied to the product and all the requirements of all relevant parts of AS/NZS 4417 applicable to the article shall be fulfilled.

**Additional Certification Conditions:** None.

## Model Details:

Model Name
Xi CR 22W 0.2-1.05A SDMP 230V C123 sXt
Xi CR 40W 0.2-1.05A SDMP 230V C123 sXt
Xi CR 75W 0.2-1.05A SDMP 230V C123 sXt

## Additional Information:

Model: Xi CR 22W 0.2-1.05A SDMP 230V C123 sXt

Ratings: Uin: 220-240 V, fn: 50/60 Hz, lin: 0.13-0.12 A, Pin: 28 W, PF: 0.9C,

Uoutput: 8-48 Vdc, Uout = 80 V max,

Irated: 200-1050 mA, Prated: 22 W, ta: -40...+60 °C, tc: 80 °C,

SELV, Built-in

Model: Xi CR 40W 0.2-1.05A SDMP 230V C123 sXt

Ratings: Uin: 220-240 V, fn: 50/60 Hz, lin: 0.22-0.20 A, Pin: 47 W, PF: 0.9C,

Uoutput: 20-77 Vdc, Uout = 100 V max,

Irated: 200-1050 mA, Prated: 40 W, ta: -40...+55 °C, tc: 85 °C,

SELV, Built-in

Model: Xi CR 75W 0.2-1.05A SDMP 230V C123 sXt

Ratings: Uin: 220-240 V, fn: 50/60 Hz, lin: 0.39-0.36 A, Pin: 84 W, PF: 0.9C,

Uoutput: 35-150 Vdc, Uout = 200 V max,

Irated: 200-1050 mA, Prated: 75 W, ta: -40...+55 °C, tc: 85 °C,

Built-in