



# Philips Ledinaire waterproof – For your everyday lighting jobs, easy to choose from the shelves and to install

## Ledinaire Waterproof

The Ledinaire waterproof (WT060) range contains a selection of popular off-the-shelf waterproof LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable. Ledinaire enables, simple and quick installation, with optional through wiring possibility.

### Benefits

- Philips quality and reliability
- Energy saving
- Diffuse comfortable light
- Easy installation, through external push in connector

### Features

- Robust (IK08) and waterproof (IP66) luminaire
- Multiple lengths and light levels available
- Mounting bracket can be positioned over full length of luminaire

# Ledinaire Waterproof

## Application

- Covered car parks
- Industrial halls (up to 4 m in height)
- Storage rooms


## Versions



Ledinaire Waterproof


## Dimensional drawing

WT060C



WT060C	A	B	C	D	E	F	G
L100	80	30	30	100	100	100	100
L150	80	30	30	150	100	100	100
L200	80	30	30	200	100	100	100
L250	80	30	30	250	100	100	100
L300	80	30	30	300	100	100	100

WT060C TW



WT060C TW	A	B	C	D	E	F
L100	80	30	30	100	100	100
L150	80	30	30	150	100	100
L200	80	30	30	200	100	100

## Product details



Ledinaire waterproof, WT060C



Ledinaire waterproof, WT060C



Ledinaire waterproof, WT060C



Ledinaire waterproof, WT060C



Ledinaire waterproof, WT060C



Ledinaire waterproof, WT060C

# Ledinaire Waterproof

## General Information

Driver included	Yes
Light source replaceable	No
Number of gear units	1 unit
Service tag	No

## Light Technical

Beam angle of light source	120 degree(s)
Color rendering index (CRI)	>80
Luminous Efficacy (rated) (Nom)	120 lm/W
Optic type	Symmetrical
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	1.6

## Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz

## Temperature

Ambient temperature range	-20 to +45 °C
---------------------------	---------------

## Controls and Dimming

Dimmable	No
----------	----

## Mechanical and Housing

Housing Color	Grey
---------------	------

## Approval and Application

CE mark	CE mark
Protection class IEC	Safety class II
ENEC mark	-
Flammability mark	For mounting on normally flammable surfaces
Glow-wire test	Temperature 850 °C, duration 30 s
Mech. impact protection code	IK08
Ingress protection code	IP66

## Initial Performance (IEC Compliant)

Initial chromaticity	<5
Luminous flux tolerance	+/-10%

## Application Conditions

Maximum dim level	Not applicable
Suitable for random switching	Yes

## Light Technical

Order Code	Full Product Name	Correlated Color Temperature	
		(Nom)	Luminous Flux
911401876680	WT060C LED36S/840 PSU L1200 BN	4000 K	3,600 lm
911401876780	WT060C LED36S/840 PSU TW1 L1200 BN	4000 K	3,600 lm
911401877280	WT060C LED36S/865 PSU L1200 BN	6500 K	3,600 lm
911401892780	WT060C LED25S/840 PSU L1200 BN	4000 K	2,500 lm
911401892880	WT060C LED25S/840 PSU TW1 L1200 BN	4000 K	2,500 lm
911401876880	WT060C LED56S/840 PSU L1500 BN	4000 K	5,600 lm
911401876980	WT060C LED56S/840 PSU TW1 L1500 BN	4000 K	5,600 lm
911401877480	WT060C LED56S/865 PSU L1500 BN	6500 K	5,600 lm
911401892980	WT060C LED34S/840 PSU L1500 BN	4000 K	3,400 lm
911401893080	WT060C LED34S/840 PSU TW1 L1500 BN	4000 K	3,400 lm
911401893180	WT060C LED80S/840 PSU L1800 BN	4000 K	8,000 lm
911401876480	WT060C LED18S/840 PSU L600 BN	4000 K	1,800 lm

## Operating and Electrical

## Ledinaire Waterproof

Order Code	Full Product Name	Power Consumption
911401876680	WT060C LED36S/840 PSU L1200 BN	30 W
911401876780	WT060C LED36S/840 PSU TW1 L1200 BN	30 W
911401877280	WT060C LED36S/865 PSU L1200 BN	30 W
911401892780	WT060C LED25S/840 PSU L1200 BN	20 W
911401892880	WT060C LED25S/840 PSU TW1 L1200 BN	20 W
911401876880	WT060C LED56S/840 PSU L1500 BN	46 W

Order Code	Full Product Name	Power Consumption
911401876980	WT060C LED56S/840 PSU TW1 L1500 BN	46 W
911401877480	WT060C LED56S/865 PSU L1500 BN	46 W
911401892980	WT060C LED34S/840 PSU L1500 BN	28 W
911401893080	WT060C LED34S/840 PSU TW1 L1500 BN	28 W
911401893180	WT060C LED80S/840 PSU L1800 BN	65 W
911401876480	WT060C LED18S/840 PSU L600 BN	15 W

