



GreenPerform Panel

RC099X G2 LED38/840 W60L60 L1 W

GreenPerform Panel, 110 lm/W, 840 neutral white

GreenPerform Panel is the slimmest Panel with highest efficacy in the market. It offers two lumen options with four dimension types, 200X1200, 300X1200, 600x600,600x1200, and three mounting options, recessed, suspended and plaster ceiling.

Product data

General Information	
Light source engine type	LED
CE mark	CE mark
Light Technical	
Luminous Flux	3,800 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	110 lm/W
Color rendering index (CRI)	>80
Light source color	840 neutral white
Optical cover type	Polystyrene bowl/cover prismatic
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Power Consumption	35 W
Power Factor (Fraction)	0.9
Number of products on MCB of 16 A type B	30

Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	No
Control interface	-
Mechanical and Housing	
Housing Material	Steel
Optical cover material	Polystyrene
Housing Color	White RAL 9003
Optical cover finish	Opal
Overall length	595 mm
Overall width	595 mm
Overall height	37 mm
Dimensions (Height x Width x Depth)	37 x 595 x 595 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	-

GreenPerform Panel

Protection class IEC	Safety class II	Full product code	692382865841099
Initial Performance (IEC Compliant)		Order code	911401522822
Luminous flux tolerance	+/-10%	Material Nr. (12NC)	911401522822
Power consumption tolerance	+/-10%	Numerator - Quantity Per Pack	1
Product Data		EAN/UPC - Product/Case	6923828658410
Order product name	RC099X G2 LED38/840 W60L60 L1 W	Numerator - Packs per outer box	4
Full product name	RC099X G2 LED38/840 W60L60 L1 W	EAN/UPC - Case	6923828658410

Dimensional drawing

