



GreenPerform Batten G3 BN398C

BN398X LED20/840 L600 L1 W OP

GreenPerform batten BN398C is a cost competitive linear solution with good performance and multiple lumen output for retail and industry applications. It offers surface mount and suspension installations to cater for different mounting options. Its multiple optic designs accommodate different applications as well.

Product data

General Information		Power Factor (Fraction)	0.95
Light source engine type	LED	Number of products on MCB of 16 A type B	84
Value ladder	Performance		
Light Technical		Temperature	
Luminous Flux	2,200 lumen	Ambient temperature range	-20 to +40 °C
Correlated Color Temperature (Nom)	4000 K	Controls and Dimming	
Luminous Efficacy (rated) (Nom)	145 lm/W	Dimmable	Wireless Dim
Color rendering index (CRI)	>80	Control interface	BLE
Light source color	840 neutral white	Mechanical and Housing	
Optical cover/lens type	-	Housing Material	Steel
Operating and Electrical		Optical cover/lens material	Polymethyl methacrylate
Input Voltage	220-240 V	Housing Color	White
Line Frequency	50 or 60 Hz	Optical cover/lens finish	Frosted
Input Frequency	50 or 60 Hz	Overall length	626 mm
Power Consumption	13.5 16.5 W	Overall width	58 mm
Inrush current	8 A	Overall height	58 mm

GreenPerform Batten G3 BN398C

Dimensions (Height x Width x Depth)	58 x 58 x 626 mm
-------------------------------------	------------------

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class I
Flammability mark	-
CE mark	CE mark

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	SDCM<5
Power consumption tolerance	+/-10%

Product Data

Full product code	692382865751200
Order product name	BN398X LED20/840 L600 L1 W OP
Order code	911401549802
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material number (12NC)	911401549802
Full product name	BN398X LED20/840 L600 L1 W OP
EAN/UPC - Case	6923828657512



Dimensional drawing

