



UniStrip G4

BCP385 30LED 27K 220V 7 L52 DMX D3

UniStrip G4, 3400 lm, 60 W, Warm white, Dynamix DMX, Safety class I

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

General Information	
Driver included	Yes
Lighting Technology	LED
CE mark	CE mark
Flammability mark	For mounting on normally flammable surfaces
Light Technical	
Luminous Flux	3,400 lm
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	57 lm/W
Color rendering index (CRI)	80
Light source color	Warm white

Optical cover type	Tempered glass
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	60 A
Power Consumption	60 W
Power Factor (Fraction)	0.9
Connection	Flying leads/wires and 2 Push-in connector 4-pole

UniStrip G4

Cable	Cable 0,3 m without plug 3-pole + 2 Cables 0,3 m with connector 4-pole
--------------	--

Temperature

Ambient temperature range	-40 to +50 °C
----------------------------------	---------------

Controls and Dimming

Dimmable	Yes
-----------------	-----

Control interface	Dynamix DMX
--------------------------	-------------

Mechanical and Housing

Housing Material	Aluminum extruded
-------------------------	-------------------

Optical cover material	Polymethyl methacrylate
-------------------------------	-------------------------

Housing Color	Dark gray
----------------------	-----------

Effective projected area	0.135 m ²
---------------------------------	----------------------

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
--------------------------------	--

Mech. impact protection code	IK06 [1 J]
-------------------------------------	------------

Protection class IEC	Safety class I
-----------------------------	----------------

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
--------------------------------	--------

Initial chromaticity	SDCM = 4
-----------------------------	----------

Power consumption tolerance	+/-10%
------------------------------------	--------

Product Data

Order product name	BCP385 30LED 27K 220V 7 L52 DMX D3
---------------------------	------------------------------------

Full product name	BCP385 30LED 27K 220V 7 L52 DMX D3
--------------------------	------------------------------------

Full product code	871951492227399
--------------------------	-----------------

Order code	911401736903
-------------------	--------------

Material Nr. (12NC)	911401736903
----------------------------	--------------

Numerator - Quantity Per Pack	1
--------------------------------------	---

EAN/UPC - Product/Case	8719514922273
-------------------------------	---------------

Numerator - Packs per outer box	2
--	---

EAN/UPC - Case	8719514922273
-----------------------	---------------

Dimensional drawing

