



# UniStrip G4

## BCP385 60LED 30K 220V 7 L100 D3

UniStrip G4, 6810 lm, 120 W, Warm white, Safety class I

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

### Warnings and Safety

- For outdoor use only

### Product data

General Information	
Driver included	Yes
Lighting Technology	LED
CE mark	CE mark
Flammability mark	For mounting on normally flammable surfaces

  

Light Technical	
Luminous Flux	6,810 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	57 lm/W
Color rendering index (CRI)	80
Light source color	Warm white
Optical cover type	Tempered glass

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	70 A
Power Consumption	120 W
Power Factor (Fraction)	0.9
Connection	Flying leads/wires
Cable	Cable 0.3 m without plug 3-pole

  

Temperature	
Ambient temperature range	-40 to +50 °C

  

Controls and Dimming	
Dimmable	No

# UniStrip G4

Control interface	-
-------------------	---

## Mechanical and Housing

Housing Material	Aluminum extruded
Optical cover material	Polymethyl methacrylate
Housing Color	Dark gray
Effective projected area	0.135 m <sup>2</sup>

## Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class I

## Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
-------------------------	--------

Initial chromaticity	SDCM = 4
Power consumption tolerance	+/-10%

## Product Data

Order product name	BCP385 60LED 30K 220V 7 L100 D3
Full product name	BCP385 60LED 30K 220V 7 L100 D3
Full product code	871951492345499
Order code	911401737173
Material Nr. (12NC)	911401737173
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514923454
Numerator - Packs per outer box	2
EAN/UPC - Case	8719514923454

## Dimensional drawing

