



UniFlood M G2

BVP353 24LED RGBWW 220V L24 15 DMX

UniFlood M G2, 2465 lumen, 50 W

Philips UniFlood M gen2 is a cost-effective, exterior-rated architectural LED floodlight that's designed for façade, landscape and outdoor flood lighting applications. The robust, modular, rectangular design features highly-efficient optics, making it ideal for illuminating everything from multi-storey façades and bridges to landmarks and monuments. This LED floodlight is available in white, monochromatic colors, RGB, RGBW and tunable white. It comes with six different spread lenses ranging from narrow spot to wide flood and has DMX512/RDM control option. A truly modular floodlight that gives architects and designers the freedom to explore a wide range of concepts and designs with no limitations.

Warnings and Safety

- For outdoor use only.

Product data

| General Information | | Optical cover/lens type | |
|------------------------------------|---|--------------------------|--|
| Driver included | Yes | Clear glass | |
| Lighting Technology | | Operating and Electrical | |
| Lighting Technology | LED | Line Frequency | 50 to 60 Hz |
| CE mark | CE mark | Input Voltage | 220 to 240 V |
| Flammability mark | For mounting on normally flammable surfaces | Power Consumption | 50 W |
| Light Technical | | Power Factor (Fraction) | 0.9 |
| Luminous Flux | 2,465 lumen | Connection | Flying leads/wires and 2 Push-in connector 4-pole |
| Correlated Color Temperature (Nom) | - | Cable | Cable 0.5 m without plug 3-pole and 2 Cables 0.5 m with connector 4-pole |
| Luminous Efficacy (rated) (Nom) | 49 lm/W | | |
| Color rendering index (CRI) | >80 | | |
| Light source color | RGBW | | |

UniFlood M G2

Temperature

Ambient temperature range -40 to +50 °C

Controls and Dimming

Dimmable Yes

Control interface Dynamic DMX/RDM

Mechanical and Housing

Housing Material Aluminum extruded

Optical cover/lens material Acrylate

Housing Color Dark gray

Overall length 238 mm

Overall width 140 mm

Overall height 149 mm

Effective projected area 0.038 m²

Dimensions (Height x Width x Depth) 149 x 140 x 238 mm

Approval and Application

Ingress protection code IP66 [Dust penetration-protected, jet-proof]

Mech. impact protection code IK06 [1 J]

Protection class IEC Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance +/-10%

Power consumption tolerance +/-10%

Product Data

Full product code 871951492587899

Order product name BVP353 24LED RGBWW 220V L24 15 DMX

Order code 911401746663

Numerator - Quantity Per Pack 1

Numerator - Packs per outer box 8

Material Nr. (12NC) 911401746663

Full product name BVP353 24LED RGBWW 220V L24 15 DMX

EAN/UPC - Case 8719514925878

EAN/UPC - Product/Case 8719514925878

Dimensional drawing

