



# UniFlood M G2

## BVP353 32LED RGBWW 220V L30 10 DMX

UniFlood M G2, 2855 lumen, 60 W

Philips UniFlood M gen2 is a cost-effective, exterior-rated architectural LED floodlight that's designed for façade, landscape and outdoor flood lighting applications. The robust, modular, rectangular design features highly-efficient optics, making it ideal for illuminating everything from multi-storey façades and bridges to landmarks and monuments. This LED floodlight is available in white, monochromatic colors, RGB, RGBW and tunable white. It comes with six different spread lenses ranging from narrow spot to wide flood and has DMX512/RDM control option. A truly modular floodlight that gives architects and designers the freedom to explore a wide range of concepts and designs with no limitations.

### Warnings and Safety

- For outdoor use only.

### Product data

General Information		Optical cover/lens type	Clear glass
CE mark	CE mark	<b>Operating and Electrical</b>	
Driver included	Yes	Line Frequency	50 to 60 Hz
Flammability mark	For mounting on normally flammable surfaces	Input Voltage	220 to 240 V
Lighting Technology	LED	Power Consumption	60 W
<b>Light Technical</b>		Power Factor (Fraction)	0.9
Luminous Flux	2,855 lumen	Connection	Flying leads/wires and 2 Push-in connector 4-pole
Correlated Color Temperature (Nom)	-	Cable	Cable 0.5 m without plug 3-pole and 2 Cables 0.5 m with connector 4-pole
Luminous Efficacy (rated) (Nom)	48 lm/W		
Color rendering index (CRI)	>80		
Light source color	RGBW		

# UniFlood M G2

## Temperature

Ambient temperature range -40 to +50 °C

## Controls and Dimming

Dimmable Yes

Control interface Dynamic DMX/RDM

## Mechanical and Housing

Housing Material Aluminum extruded

Optical cover/lens material Acrylate

Housing Color Dark gray

Overall length 293 mm

Overall width 140 mm

Overall height 149 mm

Effective projected area 0.047 m<sup>2</sup>

Dimensions (Height x Width x Depth) 149 x 140 x 293 mm

## Approval and Application

Ingress protection code IP66 [Dust penetration-protected, jet-proof]

Mech. impact protection code IK06 [1 J]

Protection class IEC Safety class I

## Initial Performance (IEC Compliant)

Luminous flux tolerance +/-10%

Power consumption tolerance +/-10%

## Product Data

Full product code 871951492614199

Order product name BVP353 32LED RGBWW 220V L30 10 DMX

Order code 911401746933

Numerator - Quantity Per Pack 1

Numerator - Packs per outer box 4

Material Nr. (12NC) 911401746933

Full product name BVP353 32LED RGBWW 220V L30 10 DMX

EAN/UPC - Case 8719514926141

## Dimensional drawing

