



Xitanium LED downlight and spotlight drivers

Xi 26W/a 0.5-0.65A 40V DS 3CW 230V

Xitanium LED drivers are leading the way in terms of reliability

Product data

General Information	
Lighting Technology	LED
Operating and Electrical	
Output Current Ripple (Max)	4 %
Output Current (Max)	650 mA
Open Circuit Voltage (DC) (Max)	60 V
Output Power (Max)	26 W
Output Power (Min)	15 W
Output Current (Min)	500 mA
Output Voltage (Max)	40 V
Output Voltage (Min)	30 V
System characteristics	
Central DC Operation	No
YellowDot ready	No
Temperature	
T-Case Lifetime (Max)	75 °C
T-Case Maximum (Max)	85 °C

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Product Length	162 mm
Overall length	162 mm
Overall width	31 mm
Overall height	41.4 mm
Dimensions (Height x Width x Depth)	41 x 31 x 162 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Isolation Classification	Class I
Approval Marks	CE marking CB Certificate ENEC certificate CCC certificate RCM compliance
Output Current Set Options	Dipswitch
Protection class IEC	Safety class I
Product Data	
Full product code	692234191938100
Order product name	Xi 26W/a 0.5-0.65A 40V DS 3CW 230V

Xtanium LED downlight and spotlight drivers

Order code	929002849580
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	40
Material Nr. (12NC)	929002849580

Full product name	Xi 26W/a 0.5-0.65A 40V DS 3CW 230V
EAN/UPC - Case	6922341919398

