



# The most cost-effective outdoor spot light with better efficient and performance

## UniPoint

Our UniPoint is designed to produce both general and accent lighting while concealing the body of the device, allowing only the light to be exposed. This design can be used to change the surroundings by adding subtle or dramatic contrasting effects. It also includes exclusive features such as energy efficiency, chromatic quality and miniaturization. We guarantee extreme reliability and high level of resistance to adverse weather conditions and vandalism

### Benefits

- In stylish and very compact design
- Price point versus PHILIPS standards
- Effortless and flexible installation
- Customizing for you

### Features

- High quality LED
- Different choice of light source and beam angles
- Die-cast aluminum housing + dark grey sand coating to ensure anticorrosion
- Structural waterproof technology
- IP66
- IK06
- Quality and reliability in line with all regulations

## Application

- Buildings
- Statues
- Columns
- Pillars
- Eaves

## Versions



UniPoint BGP312 1ED



UniPoint BGP312 3LED



UniPoint BGP312 5LED

### Approval and Application

Mech. impact protection code	IK06
------------------------------	------

### Controls and Dimming

Dimmable	No
----------	----

### General Information

Optical cover/lens type	Glass bowl/cover
-------------------------	------------------

Driver included	No
-----------------	----

Light source replaceable	No
--------------------------	----

### Initial Performance (IEC Compliant)

Init. Color Rendering Index	>75
-----------------------------	-----

### Light Technical

Standard tilt angle side entry	-
--------------------------------	---

Standard tilt angle posttop	-
-----------------------------	---

### Mechanical and Housing

Color	Dark gray
-------	-----------

### General Information

Order Code	Full Product Name	Luminaire light beam spread	CE mark	Light source color	Optic type
911401710642	BGP312 1LED 2700K NB	10°	-	827 warm white	Narrow beam angle 10°
911401710652	BGP312 1LED 2700K MB	25°	-	827 warm white	Medium beam angle 25°
911401710662	BGP312 1LED 2700K WB	40°	-	827 warm white	Wide beam angle 42°
911401710672	BGP312 1LED 3000K NB	10°	-	830 warm white	Narrow beam angle 10°
911401710682	BGP312 1LED 3000K MB	25°	-	830 warm white	Medium beam angle 25°
911401710692	BGP312 1LED 3000K WB	40°	-	830 warm white	Wide beam angle 42°
911401710702	BGP312 1LED 4000K NB	10°	-	840 neutral white	Narrow beam angle 10°
911401710712	BGP312 1LED 4000K MB	25°	-	840 neutral white	Medium beam angle 25°
911401710722	BGP312 1LED 4000K WB	40°	-	840 neutral white	Wide beam angle 42°
911401711442	BGP312 1LED 2700K NB GG	10°	CE mark	827 warm white	Narrow beam angle 10°
911401711452	BGP312 1LED 2700K MB GG	25°	CE mark	827 warm white	Medium beam angle 25°
911401711462	BGP312 1LED 2700K WB GG	40°	CE mark	827 warm white	Wide beam angle 42°
911401711472	BGP312 1LED 3000K NB GG	10°	CE mark	830 warm white	Narrow beam angle 10°
911401711482	BGP312 1LED 3000K MB GG	25°	CE mark	830 warm white	Medium beam angle 25°
911401711492	BGP312 1LED 3000K WB GG	40°	CE mark	830 warm white	Wide beam angle 42°

Order Code	Full Product Name	Luminaire			
		light beam spread	CE mark	Light source color	Optic type
911401711502	BGP312 1LED 4000K NB GG	10°	CE mark	840 neutral white	Narrow beam angle 10°
911401711512	BGP312 1LED 4000K MB GG	25°	CE mark	840 neutral white	Medium beam angle 25°
911401711522	BGP312 1LED 4000K WB GG	40°	CE mark	840 neutral white	Wide beam angle 42°
911401710732	BGP312 3LED 2700K NB	10°	-	827 warm white	Narrow beam angle 10°
911401710742	BGP312 3LED 2700K MB	25°	-	827 warm white	Medium beam angle 25°
911401710752	BGP312 3LED 2700K WB	40°	-	827 warm white	Wide beam angle 42°
911401710762	BGP312 3LED 3000K NB	10°	-	830 warm white	Narrow beam angle 10°
911401710772	BGP312 3LED 3000K MB	25°	-	830 warm white	Medium beam angle 25°
911401710782	BGP312 3LED 3000K WB	40°	-	830 warm white	Wide beam angle 42°
911401710792	BGP312 3LED 4000K NB	10°	-	840 neutral white	Narrow beam angle 10°
911401710802	BGP312 3LED 4000K MB	25°	-	840 neutral white	Medium beam angle 25°
911401710812	BGP312 3LED 4000K WB	40°	-	840 neutral white	Wide beam angle 42°
911401711532	BGP312 3LED 2700K NB GG	10°	CE mark	827 warm white	Narrow beam angle 10°
911401711542	BGP312 3LED 2700K MB GG	25°	CE mark	827 warm white	Medium beam angle 25°
911401711552	BGP312 3LED 2700K WB GG	40°	CE mark	827 warm white	Wide beam angle 42°
911401711562	BGP312 3LED 3000K NB GG	10°	CE mark	830 warm white	Narrow beam angle 10°
911401711572	BGP312 3LED 3000K MB GG	25°	CE mark	830 warm white	Medium beam angle 25°
911401711582	BGP312 3LED 3000K WB GG	40°	CE mark	830 warm white	Wide beam angle 42°
911401711592	BGP312 3LED 4000K NB GG	10°	CE mark	840 neutral white	Narrow beam angle 10°
911401711602	BGP312 3LED 4000K MB GG	25°	CE mark	840 neutral white	Medium beam angle 25°
911401711612	BGP312 3LED 4000K WB GG	40°	CE mark	840 neutral white	Wide beam angle 42°
911401710822	BGP312 5LED 2700K NB	10°	-	827 warm white	Narrow beam angle 10°
911401710832	BGP312 5LED 2700K MB	25°	-	827 warm white	Medium beam angle 25°
911401710842	BGP312 5LED 2700K WB	40°	-	827 warm white	Wide beam angle 42°
911401710852	BGP312 5LED 3000K NB	10°	-	830 warm white	Narrow beam angle 10°
911401710862	BGP312 5LED 3000K MB	25°	-	830 warm white	Medium beam angle 25°
911401710872	BGP312 5LED 3000K WB	40°	-	830 warm white	Wide beam angle 42°
911401710882	BGP312 5LED 4000K NB	10°	-	840 neutral white	Narrow beam angle 10°
911401710892	BGP312 5LED 4000K MB	25°	-	840 neutral white	Medium beam angle 25°
911401710902	BGP312 5LED 4000K WB	40°	-	840 neutral white	Wide beam angle 42°
911401711622	BGP312 5LED 2700K NB GG	10°	CE mark	827 warm white	Narrow beam angle 10°

Order Code	Full Product Name	Luminaire light beam			
		spread	CE mark	Light source color	Optic type
911401711632	BGP312 5LED 2700K MB GG	25°	CE mark	827 warm white	Medium beam angle 25°
911401711642	BGP312 5LED 2700K WB GG	40°	CE mark	827 warm white	Wide beam angle 42°
911401711652	BGP312 5LED 3000K NB GG	10°	CE mark	830 warm white	Narrow beam angle 10°
911401711662	BGP312 5LED 3000K MB GG	25°	CE mark	830 warm white	Medium beam angle 25°
911401711672	BGP312 5LED 3000K WB GG	40°	CE mark	830 warm white	Wide beam angle 42°
911401711682	BGP312 5LED 4000K NB GG	10°	CE mark	840 neutral white	Narrow beam angle 10°
911401711692	BGP312 5LED 4000K MB GG	25°	CE mark	840 neutral white	Medium beam angle 25°
911401711702	BGP312 5LED 4000K WB GG	40°	CE mark	840 neutral white	Wide beam angle 42°

**Initial Performance (IEC Compliant)**

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial luminous flux
911401710642	BGP312 1LED 2700K NB	2700 K	120 lm
911401710652	BGP312 1LED 2700K MB	2700 K	120 lm
911401710662	BGP312 1LED 2700K WB	2700 K	120 lm
911401710672	BGP312 1LED 3000K NB	3000 K	120 lm
911401710682	BGP312 1LED 3000K MB	3000 K	120 lm
911401710692	BGP312 1LED 3000K WB	3000 K	120 lm
911401710702	BGP312 1LED 4000K NB	4000 K	120 lm
911401710712	BGP312 1LED 4000K MB	4000 K	120 lm
911401710722	BGP312 1LED 4000K WB	4000 K	120 lm
911401711442	BGP312 1LED 2700K NB GG	2700 K	120 lm
911401711452	BGP312 1LED 2700K MB GG	2700 K	120 lm
911401711462	BGP312 1LED 2700K WB GG	2700 K	120 lm
911401711472	BGP312 1LED 3000K NB GG	3000 K	120 lm
911401711482	BGP312 1LED 3000K MB GG	3000 K	120 lm
911401711492	BGP312 1LED 3000K WB GG	3000 K	120 lm
911401711502	BGP312 1LED 4000K NB GG	4000 K	120 lm
911401711512	BGP312 1LED 4000K MB GG	4000 K	120 lm
911401711522	BGP312 1LED 4000K WB GG	4000 K	120 lm
911401710732	BGP312 3LED 2700K NB	2700 K	330 lm
911401710742	BGP312 3LED 2700K MB	2700 K	330 lm
911401710752	BGP312 3LED 2700K WB	2700 K	330 lm
911401710762	BGP312 3LED 3000K NB	3000 K	330 lm
911401710772	BGP312 3LED 3000K MB	3000 K	330 lm
911401710782	BGP312 3LED 3000K WB	3000 K	330 lm
911401710792	BGP312 3LED 4000K NB	4000 K	330 lm
911401710802	BGP312 3LED 4000K MB	4000 K	330 lm
911401710812	BGP312 3LED 4000K WB	4000 K	330 lm

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial luminous flux
911401711532	BGP312 3LED 2700K NB GG	2700 K	330 lm
911401711542	BGP312 3LED 2700K MB GG	2700 K	330 lm
911401711552	BGP312 3LED 2700K WB GG	2700 K	330 lm
911401711562	BGP312 3LED 3000K NB GG	3000 K	330 lm
911401711572	BGP312 3LED 3000K MB GG	3000 K	330 lm
911401711582	BGP312 3LED 3000K WB GG	3000 K	330 lm
911401711592	BGP312 3LED 4000K NB GG	4000 K	330 lm
911401711602	BGP312 3LED 4000K MB GG	4000 K	330 lm
911401711612	BGP312 3LED 4000K WB GG	4000 K	330 lm
911401710822	BGP312 5LED 2700K NB	2700 K	595 lm
911401710832	BGP312 5LED 2700K MB	2700 K	595 lm
911401710842	BGP312 5LED 2700K WB	2700 K	595 lm
911401710852	BGP312 5LED 3000K NB	3000 K	595 lm
911401710862	BGP312 5LED 3000K MB	3000 K	595 lm
911401710872	BGP312 5LED 3000K WB	3000 K	595 lm
911401710882	BGP312 5LED 4000K NB	4000 K	595 lm
911401710892	BGP312 5LED 4000K MB	4000 K	595 lm
911401710902	BGP312 5LED 4000K WB	4000 K	595 lm
911401711622	BGP312 5LED 2700K NB GG	2700 K	595 lm
911401711632	BGP312 5LED 2700K MB GG	2700 K	595 lm
911401711642	BGP312 5LED 2700K WB GG	2700 K	595 lm
911401711652	BGP312 5LED 3000K NB GG	3000 K	595 lm
911401711662	BGP312 5LED 3000K MB GG	3000 K	595 lm
911401711672	BGP312 5LED 3000K WB GG	3000 K	595 lm
911401711682	BGP312 5LED 4000K NB GG	4000 K	595 lm
911401711692	BGP312 5LED 4000K MB GG	4000 K	595 lm
911401711702	BGP312 5LED 4000K WB GG	4000 K	595 lm

