



# Dimmable high Performance LED downlight for indoors

## GreenPerform DN391/392/393/394/395 downlight

GreenPerform is a high performance Led downlight family suitable for use in a series of Lighting applications in Office, Retail and General Area Lighting. Available in a wide variety of lumen packs, color temp and options of all type of dimming(Phase Cut/Analogue/DALI), GreenPerform becomes the perfect solution for downlight applications for professional users.

### Benefits

- Multiple options in Dimming
- Wide range of lumen pack and CCT
- Long life of 50K hours
- High colour consistency

### Features

- Aluminium heat sink for better heat dissipation
- Higher life class of 50K burning hour
- Available in both Dimming & fixed output
- Low Energy consumption- High Efficacy more than 100lm/ Watt
- Suitable for low ceiling heights
- Wide range of lumen packs ( 600lm-2000lm)

## GreenPerform DN391/392/393/394/395 downlight

### Application

- Office Lighting
- Shop/Showroom Lighting
- Corridor Lighting
- Meeting & conference room lighting
- Reception & general area Lighting

### Warnings and Safety

- Meant for use in Indoor environment only

### Versions



# GreenPerform DN391/392/393/394/395 downlight

## Application Conditions

Ambient temperature range 0 to +45 °C

## Approval and Application

Mech. impact protection code IK02

Ingress protection code IP20

## Controls and Dimming

Dimmable Yes

## Operating and Electrical

Input Voltage 220-240 V

## General Information

Beam angle of light source 120 °

Protection class IEC Safety class I (I)

Optical cover/lens type Polycarbonate

Driver included Yes

Flammability mark F

Optic type No

## Initial Performance (IEC Compliant)

Init. Color Rendering Index >80

Initial LED luminaire efficacy 100 lm/W

Initial luminous flux 1000 lm

Initial input power 10.6 W

## Mechanical and Housing

Color White

## Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Color Temperature
919515810467	DN 392B LED 10S-4000 PSD WH	6500 K
919515810471	DN 392B LED 10S-3000 PSD WH	3000 K

