



Provides soft, warm light and 3 wattage settings

LED 3-Way

Philips LED A-shape light bulb provides omni-directional light perfect for general room lighting. This lamp creates a comfortable atmosphere by providing 3 wattage levels of soft, white light that will not fade fabrics or furnishings.

Benefits

- Long life -- lowers maintenance costs by reducing re-lamp frequency
- Excellent color consistency with high 80+ color rendering (CRI)
- 3-Way switching to get exactly the right amount of light when you need it

Features

- Light equivalent to 3 standard incandescent bulb outputs when used with a standard 3-way socket or luminaire
- 25,000-hour rated average life
- Instant on
- ENERGY STAR qualified
- Emits virtually no UV/IR light in the beam

Application

- Hotels/Motels
- Residential & Assisted Living


LED 3-Way

Versions



Single Contact Medium Screw A21
(A21) Frosted

Dimensional drawing



Product	D	C
18.5A21/LED/927/P/E26/3WAY ND 4/1FB T20	70.6 mm	133.1 mm
14A21/LED/927/P/E26/3WAY ND 4/1FB T20	70.6 mm	133.1 mm
18.5A21/LED/927/P/E26/3WAY ND 4/1FB T20	70.6 mm	133.1 mm
14A21/LED/927/P/E26/3WAY ND 4/1FB T20	70.6 mm	133.1 mm

Controls and Dimming

Dimmable	No
----------	----

Operating and Electrical

Input Frequency	60 Hz
Voltage (Nom)	120 V
Starting Time (Nom)	0.5 s

General Information

Cap-Base	E26
Switching Cycle	50000X

Light Technical

Beam Angle (Nom)	250 °
Color Code	927
Correlated Color Temperature (Nom)	2700 K
Color Rendering Index (Nom)	90
Llmf At End Of Nominal Lifetime (Nom)	70 %

Mechanical and Housing

Bulb Finish	Frosted
Bulb Shape	A21 (A21)

Operating and Electrical

Order Code	Full Product Name	Wattage Equivalent	Power (Rated) (Nom)
929002285003	14A21/LED/927/P/E26/3WAY ND 4/1FB T20	100-60-40 W	14, 8, 5 W
929002285005	14A21/LED/927/P/E26/3WAY ND 4/1FB T20	100-60-40 W	14, 8, 5 W
929002285103	18.5A21/LED/927/P/E26/3WAY ND 4/1FB T20	150-100-50 W	18.5, 13, 6 W
929002285105	18.5A21/LED/927/P/E26/3WAY ND 4/1FB T20	150-100-50 W	18.5, 13, 6 W

General Information

LED 3-Way

Order Code	Full Product Name	Nominal Lifetime (Nom)
929002285003	14A21/LED/927/P/E26/3WAY ND 4/1FB T20	25000 h
929002285005	14A21/LED/927/P/E26/3WAY ND 4/1FB T20	25000 h

Order Code	Full Product Name	Nominal Lifetime (Nom)
929002285103	18.5A21/LED/927/P/E26/3WAY ND 4/1FB T20	15000 h
929002285105	18.5A21/LED/927/P/E26/3WAY ND 4/1FB T20	15000 h

Light Technical

Order Code	Full Product Name	Luminous Flux (Nom)
929002285003	14A21/LED/927/P/E26/3WAY ND 4/1FB T20	1600-800-450 lm
929002285005	14A21/LED/927/P/E26/3WAY ND 4/1FB T20	1600-800-450 lm

Order Code	Full Product Name	Luminous Flux (Nom)
929002285103	18.5A21/LED/927/P/E26/3WAY ND 4/1FB T20	2150-1600-620 lm
929002285105	18.5A21/LED/927/P/E26/3WAY ND 4/1FB T20	2150-1600-620 lm

Temperature

Order Code	Full Product Name	T-Case Maximum (Nom)
929002285003	14A21/LED/927/P/E26/3WAY ND 4/1FB T20	80 °C
929002285005	14A21/LED/927/P/E26/3WAY ND 4/1FB T20	80 °C
929002285103	18.5A21/LED/927/P/E26/3WAY ND 4/1FB T20	95 °C
929002285105	18.5A21/LED/927/P/E26/3WAY ND 4/1FB T20	95 °C

