



ZXP399 DMX Controls and Accessories

ZXP399 samples case 220V DMX

ZXP399 DMX Controls and Accessories - Aluminum

The ZXP399 DMX Controls and Wiring Accessories are to be used with our architectural and facade lighting luminaires (UniFlood C, M and G, UniStrip G4, UniEdge, UniDot G2, UniString and UniBar).;DMX Controls include main controller, stand-alone controller, sub-controllers, DMX amplifier and DMX addressing device.;Main Controller: Industrial computer that can control up to 6000 DMX universes.;Stand-alone Controller: Fits for medium applications with up to 700 DMX universes.;Wiring accessories include leader and jumper cables with male and female IP67 connectors and end-caps.;Addressing Device: Hand-held device that can write DMX addresses to a whole run on-site within minutes.;DMX Amplifier: Compact, IP65 and low power repeater that can amplify the DMX signal for up to 100 meters.

Product data

General Information	
Protection class IEC	Safety class I
CE mark	-
Material	Aluminum
Accessory color	Aluminum
Operating and Electrical	
Input Voltage	200 to 240 V

Input Frequency	50 to 60 Hz
Mechanical and Housing	
Overall length	540 mm
Overall width	390 mm
Overall height	240 mm

ZXP399 DMX Controls and Accessories

Approval and Application

Ingress protection code IP20 [Finger-protected]


Product Data

Full product code 911401772862
Order product name ZXP399 samples case 220V DMX
Order code 911401772862

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401772862
Net Weight (Piece)	14.000 kg



Dimensional drawing



Electrical accessory

