



SmartBright G2 LED Floodlight

BVP151 LED100/CW 220-240V 100W AWB CQC

SmartBright G2 LED Floodlight delivers high lumen efficacy, with long lifetime and reliable design. Asymmetric optical distribution improves light effect. The product is an ideal solution for most floodlight applications.

Product data

General Information	
Light source color	757 cool white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	Flat glass
Control interface	-
Connection	Flying leads/wires
Cable	Cable 0.6 m without plug
Protection class IEC	Safety class I
Flammability mark	-
CE mark	-
Optic type outdoor	Asymmetrical
Light source engine type	LED
Serviceability class	Class C, luminaire without serviceable parts, not serviceable
Light Technical	
Standard tilt angle posttop	-
Standard tilt angle side entry	-

Operating and Electrical	
Input Voltage	220-240 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.9
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing Material	Aluminum die cast
Optical cover/lens material	Tempered glass
Mounting device	Mounting bracket adjustable
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	360 mm
Overall width	273 mm
Overall height	58 mm
Color	Dark gray
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]

SmartBright G2 LED Floodlight

Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Luminaire surge protection level until 4 kV differential mode and 4 kV common mode

Initial Performance (IEC Compliant)


Initial luminous flux (system flux)	10000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	100 lm/W
Init. Corr. Color Temperature	5700 K
Init. Color Rendering Index	80
Initial input power	100 W
Power consumption tolerance	+/-10%

Application Conditions


Ambient temperature range	-25 to +40 °C
---------------------------	---------------

Product Data

Full product code	692382863402599
Order product name	BVP151 LED100/CW 220-240V 100W AWB CQC
EAN/UPC - Product	6923828634025
Order code	911401814380
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	911401814380
Net Weight (Piece)	3.180 kg



Dimensional drawing



BVP151 LED Underwater

