



MASTER PL-C Xtra 4 Pin

MASTER PL-C Xtra 26W/840/4P 1CT/5X10CC

Energy-saving compact fluorescent lamps Compact long-arc low-pressure mercury discharge lamp Envelope consists of 4 parallel narrow fluorescent tubes

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Correlated Colour Temperature (Nom)	
Cap base	G24Q-3 [G24q-3]	Luminous efficacy (rated) (nom.)	75 lm/W
Life to 50% failures preheat (nom.)	33000 h	Colour rendering index (nom.)	82
LSF preheat 2,000 hours rated	99 %	LLMF 2000 h Rated	92 %
LSF preheat 4,000 hours rated	98 %	LLMF 4000 h Rated	88 %
LSF preheat 6,000 hours rated	97 %	LLMF 6000 h Rated	86 %
LSF preheat 8,000 hours rated	96 %	LLMF 8000 h Rated	84 %
LSF preheat 16,000 hours rated	94 %	LLMF 12000 h Rated	81 %
LSF preheat 20,000 hours rated	90 %	LLMF 16000 h Rated	79 %
		LLMF 20000 h Rated	78 %
Light Technical		Operating and Electrical	
Colour Code	840 [CCT of 4,000 K]	Power (Rated) (Nom)	26.0 W
Luminous flux (nom.)	1800 lm	Lamp current (nom.)	0.300 A
Luminous flux (rated) (nom.)	1800 lm		
Colour designation	Cool White (CW)		

MASTER PL-C Xtra 4 Pin

Temperature

Design temperature (nom.) 28 °C

Controls and Dimming

Dimmable Yes

Mechanical and Housing

Cap-base information 4P

Approval and Application

Energy efficiency label (EEL) A


Mercury (Hg) content (nom.) 3.0 mg

Energy consumption kWh/1,000 hours 29 kWh

Product Data

Full product code	871150089892070
Order product name	MASTER PL-C Xtra 26W/840/4P 1CT/5X10BOX
EAN/UPC – product	8711500898920
Order code	89892070
Local code	26PLC8404PXTRA
Numerator – quantity per pack	1
SAP numerator – packs per outer box	50
Material no. (12 NC)	927906384014
SAP net weight (piece)	60.400 g
ILCOS code	FSQ-26/40/1B-E-G24q=3

Dimensional drawing




PL-C Xtra 26W/840/4P

Product

MASTER PL-C Xtra 26W/840/4P 1CT/5X10BOX

Photometric data





Lightcolour /840

Lightcolour /840



MASTER PL-C Xtra 4 Pin

Lifetime



LDLE_PLC4PLTG_0001-Life expectancy diagram

LDLE_PLC4PLTG_0002-Life expectancy diagram



LDLE_PLC4PLTG_0003-Life expectancy diagram

LDLM_PLC4PLTG_0001-Lumen maintenance diagram

