



# MASTER PL-L Xtra Polar 4 Pin

## MASTER PL-L XTRA POLAR 36W/830/4P 1CT/25

MASTER PL-L Xtra Polar is a medium to high-wattage linear compact fluorescent lamp, typically used for lower-temperature applications such as outdoor lighting and cold storage. MASTER PL-L Xtra Polar lamps furthermore provide significantly lower operating costs thanks to their lifetime, which is more than double that of a standard MASTER PL-L lamp, and their very low early failure rate. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. It is designed for operation on electromagnetic as well as HF electronic gear and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information	
Cap base	2G11 [ 2G11]
Life to 10% failures (nom.)	14000 h
Life to 50% failures (nom.)	21000 h
Life to 50% failures preheat (nom.)	36000 h
System description	na [-]
LSF 2000 h Rated	99 %
LSF 4000 h Rated	99 %

LSF 6000 h Rated	98 %
LSF 8000 h Rated	97 %
LSF 12000 h Rated	95 %
LSF 16000 h Rated	88 %
LSF 20000 h Rated	58 %
LSF preheat 2,000 hours rated	99 %
LSF preheat 4,000 hours rated	99 %
LSF preheat 6,000 hours rated	99 %

# MASTER PL-L Xtra Polar 4 Pin

LSF preheat 8,000 hours rated	99 %
LSF preheat 16,000 hours rated	97 %
LSF preheat 20,000 hours rated	94 %

## Light Technical

Colour Code	830 [ CCT of 3,000 K]
Luminous flux (nom.)	2900 lm
Luminous flux (rated) (nom.)	2900 lm
Colour designation	Warm white (WW)
Correlated Colour Temperature (Nom)	3000 K
Luminous efficacy (rated) (nom.)	81 lm/W
Colour rendering index (nom.)	>80
LLMF 2000 h Rated	94 %
LLMF 4000 h Rated	93 %
LLMF 6000 h Rated	92 %
LLMF 8000 h Rated	91 %
LLMF 12000 h Rated	90 %
LLMF 16000 h Rated	89 %
LLMF 20000 h Rated	88 %

## Operating and Electrical

Power (Rated) (Nom)	36.0 W
Lamp current (nom.)	0.445 A

## Temperature

Design temperature (nom.)	18 °C
---------------------------	-------

## Controls and Dimming

Dimmable	Yes
----------	-----

## Mechanical and Housing

Cap-base information	4P
----------------------	----

## Approval and Application

Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	3.0 mg
Energy consumption kWh/1,000 hours	40 kWh

## Product Data

Full product code	871150026776440
Order product name	MASTER PL-L XTRA POLAR 36W/830/4P 1CT/25
EAN/UPC – product	8711500267764
Order code	26776440
Local code	36PLL830XTRAPOL
Numerator – quantity per pack	1
SAP numerator – packs per outer box	25
Material no. (12 NC)	927907783015
SAP net weight (piece)	104.000 g
ILCOS code	FSD-36/30/1B-E-2G11



## Dimensional drawing

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-L XTRA POLAR 36W/830/4P 1CT/25	39.0 mm	18.0 mm	384.2 mm	410 mm	416.6 mm

PL-L Xtra 36W/830/4P LT

# MASTER PL-L Xtra Polar 4 Pin

## Photometric data



Lightcolour /830

Lightcolour /830

