



Essential LED tubes T5 Mains

CorePro LEDtube 600mm 8W840 G5 I MX

The Essential LEDtube T5 is an affordable LED solution suitable for replacing T5 fluorescent lamps. Thanks to a unique design, Philips Essential LED tube T5 Mains can be directly installed in luminaires operating on mains power connection. The product provides a natural lighting effect for use in general lighting applications, as well as instant energy savings – an environmentally friendly solution.

Product data

General Information		Lamp Current (Max)	
Cap-Base	G5 [G5]	Lamp Current (Min)	75 mA
EU RoHS compliant	Yes	Starting Time (Nom)	30 mA
Nominal Lifetime (Nom)	30000 h	Warm Up Time to 60% Light (Nom)	0.5 s
Switching Cycle	50000X	Power Factor (Nom)	0.92
Voltage (Nom)		100-240 V	
Light Technical		Temperature	
Color Code	840 [CCT of 4000K]	T-Ambient (Max)	45 °C
Beam Angle (Nom)	200 °	T-Ambient (Min)	-20 °C
Luminous Flux (Nom)	900 lm	T-Storage (Max)	65 °C
Color Designation	Cool White (CW)	T-Storage (Min)	-40 °C
Correlated Color Temperature (Nom)	4000 K	T-Case Maximum (Nom)	70 °C
Luminous Efficacy (rated) (Nom)	112.00 lm/W	Controls and Dimming	
Color Consistency	<6	Dimmable	No
Color Rendering Index (Nom)	80	Mechanical and Housing	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Product Length	600 mm
Operating and Electrical			
Input Frequency	50 to 60 Hz		
Power (Nom)	8 W		

Essential LED tubes T5 Mains

Approval and Application


Energy Efficiency Label (EEL)	A+
Energy Saving Product	Yes
Approval Marks	CE marking RoHS compliance KEMA Keur certificate
Energy Consumption kWh/1000 h	- kWh

Product Data

Full product code	871869666756900
-------------------	-----------------

Order product name	CorePro LEDtube 600mm 8W840 G5 I MX
EAN/UPC - Product	8718696667569
Order code	929001275412
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	20
Material Nr. (12NC)	929001275412
Net Weight (Piece)	0.080 kg

Dimensional drawing



TLED 100-240V 8-14W 4000K G5 ND

Product	D1	D2	A1	A2	A3
CorePro LEDtube 600mm 8W840 G5 I MX	15.8 mm	19 mm	549 mm	556.1 mm	563.2 mm

